



TRACE LITE
commercial & industrial lighting

barrontg.com



LOW-PROFILE ARCHITECTURAL WALLPACK

UL 924 Listed emergency egress models.

Integral motion detection and photocontrol options.

Architectural die-cast aluminum housing.

UL Listed for Wet Locations.

California Title 24 compliant.

SLW Series

LOW-PROFILE, ARCHITECTURAL LED WALLPACK WITH EGRESS OPTION

The slim architectural SLW Series LED wallpack features integral motion detection (PIR sensor) or photocontrol only (NS model) in both “normally on” and UL 924 Listed emergency egress models. The fully gasketed die-cast enclosure is UL Listed for Wet Locations. The SLW’s 15 Watt LED light engine delivers 1500 lumens in AC mode and 600 lumens in emergency mode. Zero uplight optics reduce light pollution.



FEATURES & BENEFITS

- Architectural die-cast aluminum housing
- Snap-fit housing to mounting plate for easy access and installation
- Universal pattern knockouts for mounting to 3” and 4” J-box
- ½” Threaded conduit entry for top feed
- Available in Bronze, Black, Silver or White finish
- EM option uses long-life, maintenance-free, rechargeable high temperature NiCad battery which includes internal heater suitable for cold locations and draws an additional 17 Watts
- Integral controls include:
 - Standard unit: Passive infrared (PIR) motion sensor with up to 10’ detection, operational from dusk to dawn. Unit will shut off after two minutes of inactivity. The light will activate in AC mode only when motion is detected. Motion sensor (PIR) and dusk to dawn operation cannot be altered
 - No PIR sensor option (NS): switchable AC operation for use as dusk to dawn with included photocontrol or use of a normally open switch by disabling photocontrol
- 15 Watt high-power LED light engine delivers 1500 lumens (600 lumens in emergency mode for 60’ on center spacing)
- Standard 4000K CCT, CRI ≥ 70, L70 > 72,000 hours
- LED array is protected by a high-impact, UV-resistant polycarbonate lens

SPECS AT A GLANCE

Wattage (W)*	15 (EM model: 32)
Lumens (lm)	1500
Efficacy (LPW)	100
Equivalency	100W HID
CCT	4000K
CRI	≥ 70
Input Voltage	120-277VAC, 60Hz
Warranty	5 Years
Certifications	UL 924 Listed for Wet Locations, NFPA 101, Title 24
Operating Temp	-25°C to 50°C (-13°F to 122°F)
Weight	3.7 lbs (EM model: 4.5 lbs)

* Nominal Wattage, tested at 5000K CCT. Values at 120/277VAC.

Note: Environment and application will affect actual performance. Typical values and 25°C (77°F) used for testing. Specifications subject to change without notice.

ORDERING INFORMATION (Example: SLW-15-4K-EM)

Series	Wattage	CCT	Finish	Options
SLW	15 = 15W	4K = 4000K	(Blank) = Bronze	EM ¹ = UL 924 Emergency battery back-up with self-test/ self-diagnostics, cold location
			BL = Black	NS ² = Photocontrol only (no PIR motion sensor)
			SV = Silver	
Notes			WH = White	
¹ EM model not DLC Qualified product				
² Without this option, this model is equipped with a motion sensor that cannot be disabled				



Specifications are subject to change without notice. Installation must be performed in accordance with Barron Lighting Group installation instructions.

10840258 MKT-LIT-SLW REV 4

BARRON
lighting group

7885 North Glen Harbor Blvd
Glendale, Arizona 85307
800.533.3948
barronlitg.com