

| Model: | Date: |
|--------------|-----------|
| Accessories: | |
| Job Name: | Type: |

Tru Blue T5 Fluorescent

GLL-65-T5HO-54 / GLL-65-T5HO-24

GLL-65-T5HO-54

| PERFORMANCE DATA | | | | |
|-----------------------|--------|----|--|--|
| Initial Lumens | 5,000 | lm | | |
| Rated Average Life | 20,000 | h | | |
| Color Temperature | 6500 | K | | |
| Color Rendering Index | 85 | | | |

| PHYSICAL DESCRIPTION | | | | |
|------------------------|------------------|-----------|--|--|
| Maximum Overall Length | 1,148 (45.2) | mm (in) | | |
| Bulb Diameter | 16 (0.625) | mm (in) | | |
| Base Designation | Miniature Bi-Pin | | | |
| Weight | .06 (.02) | lbs (kgs) | | |

^{*} Compatible fixture by others

GLL-65-T5HO-24

| PERFORMANCE DATA | | | | |
|-----------------------|--------|----|--|--|
| Initial Lumens | 2,000 | lm | | |
| Rated Average Life | 20,000 | h | | |
| Color Temperature | 6500 | K | | |
| Color Rendering Index | 85 | | | |

| PHYSICAL DESCRIPTION | | | | |
|------------------------|------------------|-----------|--|--|
| Maximum Overall Length | 536 (21.1) | mm (in) | | |
| Bulb Diameter | 16 (0.625) | mm (in) | | |
| Base Designation | Miniature Bi-Pin | | | |
| Weight | .03 (.01) | lbs (kgs) | | |

^{*} Compatible fixture by others







