

SAVE THESE INSTRUCTIONS!

READ CAREFULLY AND FOLLOW ALL INSTRUCTIONS FOR YOUR OWN SAFETY

- **DISCONNECT AC POWER SUPPLY BEFORE SERVICING.**
- Installation and servicing of this equipment should be performed by qualified service personnel only.
- Ensure the electricity connections conform to the National Electrical Code and local regulations if applicable.
- Do not mount near gas or electrical heaters.
- Equipment should be mounted in locations and at heights where it will not readily be subjected to tampering by unauthorized personnel.
- The use of accessory equipment not recommended by the manufacturer may cause an unsafe condition. Any modification or use of non-original components will void the warranty and product liability.
- Do not use this equipment for other than intended use.



INSTALLATION INSTRUCTIONS

1. Feed wire lead from 3/4" NPT knuckle into weatherproof box cover / post top fitter, whichever applies, then securely seat knuckle into box cover / post top fitter.
2. Electrical connections should be made inside junction box. Cap all unused leads to prevent shorting. This fixture auto adjust for voltages between 120VAC - 277VAC
 - a. Connect the line fixture lead to the black supply lead.
 - b. Connect the common fixture lead to the white supply lead
 - c. Connect the ground lead from the service to the green grounding screw.
3. Use approved connectors to connect fixture leads to supply leads and make wire splices inside junction box.

IMPORTANT

To weather-proof your outdoor installation, be sure to seal all holes in fixture housing. (Mounting, conduit, plugs, and photo controls, etc) with silicone sealant.