



TRACE LITE
commercial & industrial lighting

barronltg.com



ADJUSTABLE LED WALLPACK

Adjustable light bars can be aimed in any orientation.

Field-selectable CCT between 3000K, 4000K or 5000K.

Power-selectable (varies per model) up to 11,200 lumens.

DesignLights Consortium® PREMIUM Qualified

Photocontrol accessory available.

BAWX Series

ADJUSTABLE LED WALLPACK

The BAWX Series LED wallpack features adjustable light bars that can be oriented in up, down or up/down orientations to create dramatic lighting effects in any desired area. This family of product is offered with selectable CCT (3000K-4000K-5000K) and the double bar configurations also feature power selectability. Available in two sizes to complement any building exterior and to accommodate multiple mounting heights. The BAWX wallpack has efficacies up to 145 LPW and is DesignLights Consortium® PREMIUM Qualified to maximize energy savings and utility rebates. This wallpack is ideal for general outdoor lighting, commercial buildings, pathways and sidewalks.



FEATURES & BENEFITS

- Precision die-cast aluminum enclosure in a bronze powder-coat finish, UV-resistant polycarbonate optical lens
- BAWX-1 is offered with one adjustable light bar, 360° rotation, 25W offering up to 3,286 lumens
- BAWX-2 is offered with two adjustable light bars, 360° rotation, offered in two configurations;
 - 60W – power selectable (25W-40W-60W) offering between 3139 and 8400 lumens
 - 80W – power selectable (40W-60W-80W) offering between 5076 and 11,200 lumens
- Efficacies up to 145 LPW to maximize energy saving and utility rebates
- All models are CCT selectable between 3000K, 4000K, 5000K, using switch located in the backbox
- Bars can be locked into desired position using the set screw inside the light bar arm
- Enclosure is supplied with three ½” hubs; one on each side and one on the bottom
- Type VS distribution
- Housing mounts to backplate for ease of installation
- Several ½” hubs allow surface mount conduit feed
- Mounts to standard 3 ½” or 4” square electrical J-box
- UL Listed for Wet Locations, IP65 rated

SPECS AT A GLANCE

Model	BAWX-1-25	BAWX-2-60	BAWX-2-80
Wattage (W)	25W	25W-40W-60W (Switchable)	40W-60W-80W (Switchable)
Lumens (lm)	3139-3286	3139-8392	5076-11,149
Efficacy (LPW)	Up to 145 Lumens per Watt		
Distribution	Type VS		
CCT	3000K-4000K-5000K (Switchable)		
CRI	>70		
Input Voltage	120-277VAC, 50/60Hz		
Operating Temp	-20°C to 40°C (-4°F to 104°F)		
Certifications	UL Listed for Wet Locations, IP65, DLC PREMIUM (BAWX-1-25, BAWX-2-60), DLC (BAWX-2-80)		
Warranty	5 Years		

* Nominal Wattage, tested at 5000K CCT. Values at 120/277VAC.

Note: Environment and application will affect actual performance. Typical values and 25°C (77°F) used for testing. Specifications subject to change without notice.

ORDERING INFORMATION (Example: BAWX-2-60-CP-BR)

Model	Description
BAWX-1-25-C-BR	LED Adjustable Wallpack, 1 Rotatable Bar, 25W, Color Selectable 3000K-4000K-5000K CCT, Bronze Finish
BAWX-2-60-CP-BR	LED Adjustable Wallpack, 2 Rotatable Bars, Power Selectable 25W-40W-60W, Color Selectable 3000K-4000K-5000K CCT, Bronze Finish
BAWX-2-80-CP-BR	LED Adjustable Wallpack, 2 Rotatable Bars, Power Selectable 40W-60W-80W, Color Selectable 3000K-4000K-5000K CCT, Bronze Finish

Notes

¹ Order as a separate line item; shipped in separate box for field installation

Accessories¹ (Field Installed)

PCU = 120/277VAC Button Photocontrol



Specifications are subject to change without notice. Installation must be performed in accordance with Barron Lighting Group installation instructions.

10840448 MKT-LIT-BAWX Rev 4



7885 North Glen Harbor Blvd
Glendale, Arizona 85307
800.533.3948
barronlitg.com