

LED illuminated EXIT meets City of Chicago requirements. Rugged steel signs for wall, ceiling or end mount applications.

Model: \_\_\_\_\_ Date: \_\_\_\_\_  
Accessories: \_\_\_\_\_  
Job Name: \_\_\_\_\_ Type: \_\_\_\_\_

**FEATURES & BENEFITS**


- Meets City of Chicago Emergency requirements
- Enclosure constructed of rugged 20 gauge steel
- Exit illuminated with high-output, long-life white LEDs
- Translucent glass panels
- 90 minute emergency run time, 24 hour recharge time

**AVAILABLE WHILE SUPPLIES LAST**



**SPECIFICATIONS**

- Illumination:** Long-life, high-output white LEDs  
**Panel:** Translucent white glass panels with red legend  
**Housing:** Rugged 20 gauge steel  
**Input:** 120/277VAC Dual Primary, 60Hz  
**Battery:** Maintenance-free lead calcium battery  
**Operating Temp:** 15°C to 40°C (59°F to 104°F)  
**Run Time:** UL Listed 90 minute emergency run time, 24 hour recharge time  
**Mounting:** Ceiling, end or wall mount, canopy included  
**Finish:** White  
**Certifications:** Meets or exceeds UL 924, NEC requirements and NFPA 101  
**Warranty:** Any component that fails due to a manufacturing defect is guaranteed for five years with a separate five year prorated warranty on the battery. The warranty does not cover physical damage, abuse or instances of uncontrollable natural forces. See the full Exitronix warranty document for detailed information. (Terms and Conditions apply)



**ORDERING INFORMATION Example: CSXE-WB-WH-3**

Series	Power Source	Finish	Panel Code <sup>1</sup>		Accessories <sup>2</sup> (Field Installed)
			Single Face	Double Face	
CSXE	LB = AC Only	WH = White	3 = Exit	18 = Exit	ER1-KIT = 1' Pendant Mount Kit
	WB = With Battery		6 = Exit ▶	21 = Exit ◀ or ▶	ER2-KIT = 2' Pendant Mount Kit
			9 = Exit ◀	24 = Exit ◀ ▶	XG-6 = Poly Guard (Back Mount)
			12 = Exit ◀ ▶	17 = Stairs	
			2 = Stairs	20 = Stairs ◀ or ▶	
Notes			5 = Stairs ▶	23 = Stairs ◀ ▶	
<sup>1</sup> All panels supplied with red letters on a white background			8 = Stairs ◀		
<sup>2</sup> Order as separate line item			11 = Stairs ◀ ▶		

**CONSTRUCTION**

CSXE Series exits are constructed of heavy gauge steel with a white powder coated finish providing scratch- and corrosion-resistance.

**ILLUMINATION**

Exit face illumination is provided by special high-intensity, white, indirect LEDs with an estimated life of up to 100,000 hours.

**ELECTRICAL****Input**

Dual-voltage input 120 or 277VAC @ 60Hz.

**Sealed Lead Calcium Battery (WB)**

Exitronix sealed lead calcium batteries are maintenance-free with a life expectancy of five years. Sealed lead acid batteries provide a relatively large power-to-weight ratio making them ideal for emergency applications. Lead calcium batteries perform optimally in temperatures ranging from 59°F to 104°F (15°C to 40°C).

**Emergency (WB Only)**

The CSXE Series exit will operate for a minimum of 90 minutes during a loss of power with a 24 hour maximum recharge time for the battery.

**Solid-State Transfer**

The circuit features solid-state switching, eliminating concerns of damaged contact or mechanical failures associated with relays. The switching circuit detects a loss of line voltage and automatically switches to emergency mode.

**Test Button**

The test button is easy to locate and provides manual verification of the transfer circuit and emergency lamps.

**INSTALLATION**

Installs in minutes with easy-to-read instructions and detailed diagrams. No special hardware or tools necessary. Internally housed components and battery.

**CONFORMANCE TO CODES & STANDARDS**

The Series meets or exceeds the following: UL 924, NEC requirements and NFPA 101. City of Chicago Fire Code Approved.