

LED Illuminated Directional Signage informs, directs, and maintains traffic moving smoothly in congested areas, effectively guiding customers to the fastest service available.

State-of-the-art circuitry and long-life, ultra-bright LEDs combine dependable, maintenance-free operation and superior illumination even in direct sunlight.

Optional 120VAC illuminated control switches provide visual operating status for those areas open for business.

The 82 Series is ideal for many applications including:

- Bank Drive-Thrus
- Parking Facilities
- Airports
- Hospitals
- Rental Car Agencies
- Highway Toll Lanes
- Loading Docks
- Sports Arenas

FEATURES AND BENEFITS

- Suitable for Outdoor Locations
- High-intensity LEDs offer excellent visibility, even in direct sunlight
- Energy consumption is less than 10 watts
- Installs in minutes with only a screwdriver
- Standard 120VAC; Class 2 output
- High-grade, weather-resistant aluminum frame
- Impact-resistant, tinted polycarbonate cover
- Uniform illumination from all angles
- Optional illuminated operator control switches
- Optional mounting hardware for surface mount applications
- Assembled in the USA with global components

WARRANTY

Any component that fails due to a manufacturing defect is guaranteed for five years. The warranty does not cover physical damage, abuse or instances of uncontrollable natural forces. See the full Exitronix warranty document for detailed information. (Terms and conditions apply)

Model: _____ Date: _____
 Accessories: _____
 Job Name: _____ Type: _____



ORDERING INFORMATION

Example: 82-1-3-01-1

Series	Size	Finish ¹	Legend	Options (Factory Installed)	Accessories ⁴ (Field Installed)
82	1 = 32.6" x 6"	1 = Bronze	01 = Open/Closed	0 = None	SW1 = 1 Gang Switch
		2 ² = Black	02 = ATM Lane	1 ³ = Sun Visor	SW2 = 2 Gang Switch
		3 ² = Satin Aluminum	03 = ATM Only	2 = Recessed Mount	SW3 = 3 Gang Switch
			09 = Commercial	3 = Canopy Kit	SW4 = 4 Gang Switch
			13 = ATM Open/Closed Overlay		SW5 = 5 Gang Switch
					SW6 = 6 Gang Switch

Notes

- ¹ Custom finishes available, consult factory
- ² Black and Satin Aluminum are optional finishes, available at an additional cost
- ³ Available while supplies last
- ⁴ Order as separate line item

CONSTRUCTION

Designed for long-life and durability in exposed elements.

Housing: Constructed of weather- and corrosion-resistant 0.075 aluminum, secured with rust-resistant zinc fasteners.

Faceplate: Constructed of 0.045 aluminum, protected by an impact-resistant, polycarbonate cover.

Backplate: Constructed of 0.075 aluminum. 0.875" diameter knock-out provided.

FINISH

All finishes are weather-resistant. Architect's Bronze durable powder coat is standard. Optional black satin aluminum finishes are also available to enhance the appearance and blend aesthetically with any decor. Other colors are available; consult factory for details.

ILLUMINATION

Illumination is accomplished by using long-life, ultra-bright LEDs. Our direct view design provides a consistently bright, uniform illumination from all angles.

INSTALLATION

All units have been designed for easy installation, allowing for ceiling and back mounting, or to a junction box with the optional mounting canopy kit. Recessed mounting is also available with the optional mounting kit.

ELECTRONICS

State-of-the-art, solid-state design operates on less than 10 watts. Regulated, temperature compensated circuitry maintains an even illumination during voltage fluctuations. The circuitry also includes a built-in current limiting protective device against overload conditions. Operates on 120VAC.

DIMENSIONS

