

DESCRIPTION

4" Recessed downlight retrofit trim with integrated LED power supply and thermal management system. Designed to fit most standard 4" recessed housings.

SPECIFICATIONS

Construction:

- Heat sink and aluminum PCB optimize thermal management
- Durable thermoplastic construction
- E26 Medium screw-base Edison connector provides easy retrofit of incandescent housings
- 4" Square baffle snap-in (accessory)

Optics/LEDs:

- Long-life LEDs with up to 50,000 hours at 70% lumen maintenance
- Choice of 2700K (±145), 3000K (±175), 3500K (±225) or 4000K (±275) color temperatures with 80 CRI
- Produces 550-730 lumens output from luminaire
- Uses high-power, high-quality Cree LEDs

Electrical:

- LED driver dimmable down to 10% with most dimmers
- · Save 75% compared to incandescent sources
- •120VAC, 50/60Hz
- · Includes socket adapter
- •8 Watts power consumption
- Operating temperatures: -20°C to 40°C (-4°F to 104°F)

Installation:

- · Compatible with most 4" recessed cans
- · Compatible with non-insulated and airtight ceilings
- · Easy installation with integral clips
- Tool-less installation
- Compatible with <u>BL4ICLED-NND Series</u> 4" recessed housings

Testing & Compliance:

- Tested in accordance with IESNA LM79 & LM80
- ETL Listed for Wet Locations (US and Canada)
- Passes FCC Class B

Warranty:

• Five Year Warranty (Terms and Conditions Apply)

BRK-LED4-ECO Series

4" Recessed LED Retrofit Trim

Model:	 Date:
Accessories:	
Job Name:	Type:

AVAILABLE WHILE SUPPLIES LAST





Specs at a Glance				
Configuration	BRK-LED4-ECO			
Lumens (Im)	550-730			
ССТ (К)	2700K, 3000K, 3500K, 4000K			
CRI	≥80			
Input Voltage	120VAC, 50/60Hz			
Operating Temp	-20°C to 40°C (-4°F to 104°F)			
Certifications	ETL Listed, Passes FCC Class B			
Warranty	5 Years			

Note: Environment and application will affect performance. Typical values and 25°C used for testing. Specifications subject to change without notice.

Ordering Information (Example: BRK-LED4-BW-27-ECO)

Series	Color	сст	Accessory	
BRK-LED4	BW = White Baffle	27-ECO = 2700K	LED4-TRMPLT-ECO-SQ = Square Trim (snap-on)	
		3-ECO = 3000K		
		35-ECO = 3500K		
		4-ECO = 4000K		



Trim Accessory







