

DESCRIPTION

The RFX120 is a factory custom ordered product that is both an economical and versatile solution for your LED linear lighting needs. specialtyLED offers two LED output options to further help fulfill your lighting requirements - SMD2835 and SMD3056. RFX120 is extremely flexible and low profile making it perfect for many different small or restricted locations. Custom, made-to-order lengths, product is <u>not</u> field-cuttable due to ETL Listing. Mounting accessories are available for easy installation.

APPLICATIONS

- Cove lighting
- Under cabinet
- Architectural details
- Back lightingDisplay cabinets
- Display cabine
 Accent lighting

PERFORMANCE	2835	3056	
Lumen Output (Im/ft)	268-280	270-320	
Wattage (W/ft)	4.0	4.0	
Efficacy (Im/W)	67-70	67-80	
ССТ	2700K, 3000K, 350	00K, 4000K, 5000K	
CRI	90+		

TESTING & COMPLIANCE	2835	3056
Certifications	E	TL
IP Rating	IF	P65
Operating Temp	-25°C to 40°C	(-13°F to 104°F)
Warranty	Five	Years

ELECTRICAL	2835	3056	
Input Voltage	120VAC		
Max Run Length	164'	164'	
Dimming	10%		

PHYSICAL	2835	3056
LED Type	SMD2835	SMD3056
Dimensions	0.60"W x 0.24"H	
LEDs Per Foot	44	18
Factory Cut Increments	12.0"	4.0"
Roll Length	164'	
Beam Angle	120°	
Mounting	Mounting Hardware Available	

ORDERING INFORMATION

Example: RFX120-27K-164-3528


Series	ССТ	Length	LEDs	
RFX120	27K = 2700K	164 = 164'	2835 = SMD2835 LEDs	
	3K = 3000K	CC = Custom Cut (Consult Factory)	3056 = SMD3056 LEDs	
	35K = 3500K			
	4K = 4000K			
	5K = 5000K			


RFX120 Series

120V LED Ribbon Flex










ACCESSORIES (Sold Separately)

End Cap Accessories - Factory Installed (1 each per length required)





RFX120-EC End Cap



Connector Accessories - Factory Installed






Mounting Accessories



RFX120-LCH 0.31"x.72"x 4' PVC Channel



RFX120-MC Mounting Clip



RFX120-AL-LCH 0.78" x 0.78"x 4' Aluminum Base with Opaque PVC Cap

