

**NEW CONSTRUCTION DESCRIPTION**

6" Dedicated IC housing is available for New Construction and Remodel applications and suitable for direct contact with insulation. Air-Tight construction reduces energy costs by reducing the amount of air leakage through the ceiling.

**REMODEL SPECIFICATIONS**

**Construction:**

- Four remodel clips secure housing and accommodates 1/2" and 3/4" ceiling materials
- Housing adjusts from 5/8" to 1 1/8" to accommodate various ceiling thicknesses

**NEW CONSTRUCTION SPECIFICATIONS**

**Construction:**

- Galvanized steel construction with removable housing for easy access to the junction box
- Pre-installed nails in bar hangers easily install in regular and engineered lumber joints
- Adjustable bar hangers from 13 5/8" – 25" and can be repositioned 90° on plaster frame

**FEATURES:**


- Contains one (1) 1 1/4", six (6) 7/8" and four (4) romex pry-outs with strain relief
- UL listed for Damp Locations
- UL listed for feed-through/through-branch circuit wiring
- Certified under ASTM-E283 for air-tight construction
- Energy star qualified
- Meets state of California Title 24 Requirements
- Features quick-connect adapter

Model: \_\_\_\_\_ Date: \_\_\_\_\_  
Accessories: \_\_\_\_\_  
Job Name: \_\_\_\_\_ Type: \_\_\_\_\_




**Dimensions**

Remodel



New Construction



**Ordering Information**

SKUs	Description
BL9ICLED-NND	6" IC LED Recessed housing for new construction
BL9ICLED-RND	6" IC LED Recessed housing for remodel applications