



LOW-PROFILE LED COMBO EXIT/EMERGENCY UNIT

Compact, low-profile all-in-one Exit Sign/Emergency unit.

Designed for low-level mounting from 2' to 6'.

Quick wall mount installation to standard junction box.

Easy snap-out, field selectable chevrons.

California Energy Commission (CEC) T20 Compliant.



EXITRONIX
emergency lighting

barrontg.com


LOBO Series

LOW-PROFILE, THERMOPLASTIC, LED COMBO EXIT/EMERGENCY UNIT

The LOBO Series combines a low-profile, wall mount, thermoplastic exit sign with an integral LED emergency unit designed for low-level applications from 2' to 6'. The LOBO Series combination exit/emergency unit is designed for fast and easy installation and is available with either a red or green stencil face legend in a white enclosure. The LOBO Series is ideal for offices, classrooms, corridors, lobbies, and other indoor commercial spaces requiring a minimalist aesthetic for emergency lighting combined with a low-profile exit sign.

FEATURES & BENEFITS

- Compact, low-profile all-in-one exit sign/emergency unit
- Designed for low-level mounting from 2' to 6'
- Using multiple LOBO units mounted at a 6' height delivers 11' on-center spacing
- Quick wall mount installation to standard junction box
- Easy snap-out, field-selectable chevrons
- California Energy Commission (CEC) T20 Compliant
- 90 Minute emergency run time, 24 hour recharge time
- UL 924 Listed for Damp Locations



SPECIFICATIONS

Illumination:	Long-life, high-intensity, green or red LED exit sign with 3.1W (24 LEDs x 0.13W) low glare, emergency light strip
Housing:	Injection-molded UL 94 5VA flame-retardant high-impact resistant thermoplastic enclosure
Electrical Input:	120/277VAC Dual primary, 60Hz
Battery:	Maintenance-free 3.6V NiCad battery
Operating Temp:	0°C to 50°C (32°F to 122°F)
Run Time:	UL Listed 90 Minute emergency run time, 24 hour recharge time
Legend:	Fully illuminated 6" characters with 3/4" stroke and field-selectable directional chevrons
Mounting:	Surface wall mount with universal knockout pattern and keyhole slots
Finishes:	White (standard) or Black (lead times apply)
Certifications:	UL 924 Listed for Damp Locations Meets NFPA 101 Life Safety Code, NEC, OSHA California Energy Commission (CEC) Title 20 Compliant
Warranty:	Any component that fails due to a manufacturing defect is guaranteed for five years with a separate five year prorated warranty on the battery. The warranty does not cover physical damage, abuse or instances of uncontrollable natural forces. See the full Exitronix warranty document for detailed information. (Terms and Conditions apply)

ORDERING INFORMATION (Example: LOBO-R-WH)

Series	Legend Color	Finish	Accessories (Field Installed)
LOBO	G = Green Legend R = Red Legend	WH = White BL ¹ = Black	WG-S = Wire Guard (Back Mount) XG-6 = Poly Guard (Back Mount)

Notes

¹ Lead times apply, consult factory



Specifications are subject to change without notice. Installation must be performed in accordance with Barron Lighting Group installation instructions.

10840452 MKT-LIT-LOBO Rev 7

BARRON
lighting group
7885 North Glen Harbor Blvd
Glendale, Arizona 85307
800.533.3948
barronlitg.com