



TRACE LITE
commercial & industrial lighting

barrontg.com

ADJUSTABLE LED WALLPACK

Adjust fixture from 0° (pointing down) up to 90°.

Available with 3600 to 10,500 lumen packages.

DesignLights Consortium® (DLC) PREMIUM Qualified.

WTA Series

ADJUSTABLE LED WALLPACK

The WTA Series features a slim, compact, energy-efficient adjustable wallpack in lumen packages ranging from 3600 lumens to over 10,500 lumens. This adjustable wallpack allows the user to aim and set the fixture from 0° (pointing down) up to 90°, allowing for light to be aimed where it is needed. The WTA has efficacies up to 133 LPW and provides over 70% energy savings compared to HID technology, and is ideal for retail entryways, schools, medical complexes, retail entrances, any commercial buildings, and multi-family properties.



FEATURES & BENEFITS

- Housing can be adjusted from 0° to 90° for forward throw (10° increments)
- Die-cast aluminum housing in a powder coated bronze finish with stainless steel hardware
- UV-stabilized polycarbonate lens
- Hinged back box isolates drivers from LEDs and offers easy access to drivers
- Backbox includes three conduit entry points (one on top and two on the sides)
- Type III distribution pointing down (3000K – Type II)
- 27W to 80W LED models replace 100W to 320W HID for up to 70% energy savings
- Up to 10,500 lumens for a variety of applications
- Efficacies up to 133 LPW maximize energy savings and utility rebates
- Available in 3000K, 4000K and 5000K CCT
- Class 2 power supply, 120 to 277VAC, 50/60Hz
- 1-10V Dimming driver
- cULus Listed for Wet Locations
- DesignLights Consortium® (DLC) PREMIUM Qualified (verify QPL for specific models)

SPECS AT A GLANCE

Model	WTA-27	WTA-40	WTA-67	WTA-80
Wattage (W)*	27W	40W	67W	80W
Lumens (lm)	3600	5200	8800	10,500
Efficacy (LPW)	133	130	131	131
Equivalency (HID)	100W	150-175W	200-250W	250-320W
CCT (K)	3000K, 4000K, 5000K			
CRI	≥70			
Input Voltage	120-277VAC, 50/60Hz, 1-10V Dimming			
Operating Temp	-40°C to 40°C (-40°F to 104°F)			
Certifications	cULus Listed for Wet Locations, DLC PREMIUM			
Warranty	5 Years			
Weight	3.4 lbs	4.0 lbs	7.3 lbs	7.8 lbs

* Nominal Wattage, tested at 5000K CCT. Values at 120/277VAC. See performance table for more detailed lumen information.

Note: Environment and application will affect actual performance. Typical values and 25°C (77°F) used for testing. Specifications subject to change without notice.

ORDERING INFORMATION (Example: WTA-40-VS-3K-BR-PC)

Series	Wattage	Input Voltage	CCT	Finish	Options (Factory Installed)
WTA	27 = 27W	VS = 120/277VAC	3K = 3000K	BR = Bronze	PC = Button Photocontrol 120/277VAC
	40 = 40W		4K = 4000K		
	67 = 67W		5K = 5000K		
	80 = 80W				

LiteLogic Accessories¹ (Field Installed)

LE-RWE-BL-KIT² = Bluetooth Enabled Dimming Occupancy Sensor, PIR, Black Finish

LE-RWE-BL-12V-KIT³ = Bluetooth Enabled Dimming Occupancy Sensor, PIR, Includes 12V Power Adapter, Black Finish

PC = Button Photocontrol 120/277VAC

Notes

¹ Order as a separate line item, shipped in a separate box for installation in the field

² For 27W, 40W and 80W models only

³ For 67W models only



Specifications are subject to change without notice. Installation must be performed in accordance with Barron Lighting Group installation instructions.

10840409 MKT-LIT-WTA Rev 1